























- [42] J. Nocedal and Wright S.J. *Numerical Optimization*. Springer, New York, USA, 2006.
- [43] C. Cartis, N. I. M. Gould, and P. L. Toint. Adaptive cubic regularisation methods for unconstrained optimization. part I: motivation, convergence and numerical results. *Math. Program.*, 127(2):245–295, 2011.
- [44] P. L. Toint. Towards an efficient sparsity exploiting Newton method for minimization. *Sparse matrices and their uses*, page 1981, 1981.
- [45] A. Hyvärinen and E. Oja. Independent component analysis: algorithms and applications. *Neural networks*, 13(4-5):411–430, 2000.
- [46] The extended Yale Face Database b. <http://vision.ucsd.edu/leekc/ExtYaleDatabase/ExtYaleB.html>.
- [47] Columbia university image library (COIL-100). <http://www1.cs.columbia.edu/CAVE/software/softlib/coil-100.php>.
- [48] The CIFAR-100 dataset. <http://www.cs.toronto.edu/kriz/cifar.html>.
- [49] F. Porikli and O. Tuzel. Fast construction of covariance matrices for arbitrary size image windows. In *ICIP*, 2006.
- [50] O. Tuzel, F. Porikli, and P. Meer. Region covariance: a fast descriptor for detection and classification. In *ECCV*, 2006.
- [51] Y. Pang, Y. Yuan, and X. Li. Gabor-based region covariance matrices for face recognition. *IEEE Trans. Circuits Syst. Video Technol.*, 18(7):989–993, 2008.
- [52] The MNIST database. <http://yann.lecun.com/exdb/mnist/>.
- [53] Coverttype dataset. <https://archive.ics.uci.edu/ml/datasets/coverttype>.
- [54] K. Goldberg, T. Roeder, D. Gupta, and C. Perkins. Eigentaste: a constant time collaborative filtering algorithm. *Inform. Retrieval*, 4(2):133–151, 2001.
- [55] D. Gross. Recovering low-rank matrices from few coefficients in any basis. *IEEE Trans. on Inf. Theory*, 57(3):1548–1566, 2011.
- [56] R. Kueng and D. Gross. Ripless compressed sensing from anisotropic measurements. *Linear Algebra and its Applications*, 441:110–123, 2014.